



भानु नगरपालिका  
नगर कार्यपालिकाको कार्यालय



पत्र संख्या :- ०८२/०८३

चलानी नं : १५६२

फुसेटार, तनहुँ  
गण्डकी प्रदेश, नेपाल

२०७३

मिति :- २०८२/१२/१७

श्री जो जससँग सम्बन्ध राख्दछ ।

विषय: दररेट पेश गर्ने बारे ।

प्रस्तुत विषयमा यस कार्यालयको आ. व. २०८२/०८३ का लागि देहाय बमोजिमको अशक्त सहयोगी सामग्री खरिद गर्न आवश्यक रहेको हुनाले यसै सूचनासँग संलग्न स्पेशिफिकेशन बमोजिम सोको आजको मितिबाट सात दिनभित्र दररेट पेश गर्नुहुन सम्बन्धित फर्महरुलाई अनुरोध गरिन्छ ।

सामग्री विवरण:

१. Wheelchair
२. Auxillary Crutches
३. L stick
४. Commode Chair

सुरज श्रेष्ठ  
प्रमुख प्रशासकीय अधिकृत

“साहित्य, पर्यटन र कृषि क्षेत्र हाम्रो, पारौं समृद्ध र समुन्नत भानु राम्रो”

☎9856005111 Email: info@bhanumun.gov.np/bhanumunicipality@gmail.com Website:


www.bhanumun.gov.np



### Technical Specifications of Commode chair


S.N.	Purchaser's Specifications		Bidder's Compliance sheet		
			Compliance Yes/No	Deviation (if any)	Corresponding page no. of data sheet/ catalogue in support of specification
	<b>Commode chair</b>				
	<b>Manufacturer</b>				
	<b>Brand</b>				
	<b>Type / Model</b>				
	<b>Country of Origin</b>				
<b>1</b>	<b>Description of Function</b>				
1.1	Chair with or without castors, with a collection receptacle used for toileting away from the bathroom.				
<b>2</b>	<b>Operational Requirements</b>				
2.1	A commode chair with complete set.				
<b>3</b>	<b>System Configuration</b>				
3.1	Toilet chair is auxiliary equipment to facilitate the user to perform physiological functions				
<b>4</b>	<b>Technical Specifications</b>				
4.1	Dimensions of equipment to consider with sizes suitable for average population: <ul style="list-style-type: none"> <li>• Seat Width – approx. 440mm</li> <li>• Seat Depth – approx. 400mm</li> </ul>				
4.2	Min/Max Seat Height- approx 400-530mm				
4.3	Width Between Arms – approx. 470mm				
4.4	Safe weight load – approx. 150kg				
4.5	Container facility with the lid				
4.6	Height adjustable legs with Non-slip feet for grip and stability in wet conditions				
4.7	Toilet splash guard to avoid spills and splashes				
4.8	Chair shall be made of rust/corrosion-proof, waterproof, and contamination-resistant material (e.g. such as stainless steel), include a frame and seat, an open pan, and wheels or castors so that the user can self-propel, or be pushed by an attendant, over the toilet or into the shower.				
<b>5</b>	<b>Accessories, spares and consumables</b>				
5.1	All standard accessories, consumables and parts required to operate the equipment, including all standard tools and cleaning and lubrication materials, to be included in the offer. Bidders must specify the quantity of every item included in their offer (including items not specified above).				

Biomedical Engineer



<b>6</b>	<b>Operating Environment</b>			
6.1	The system offered shall be designed to be stored and to operate normally under the conditions of the purchaser's country. The conditions include Power Supply, Climate, Temperature, Humidity, etc.			
<b>7</b>	<b>Standards and Safety Requirements</b>			
7.1	Must submit ISO 9001 or ISO13485 or CE approved product			
<b>8</b>	<b>User Training</b>			
8.1	Not required			
<b>9</b>	<b>Warranty</b>			
9.1	Comprehensive warranty for 1 years after acceptance.			
<b>10</b>	<b>Maintenance Service During Warranty Period</b>			
10.1	During the warranty period supplier must ensure planned preventive maintenance (PPM) along with corrective/breakdown maintenance whenever required.			
<b>11</b>	<b>Installation and Commissioning</b>			
11.1	The bidder must arrange for the equipment to be installed and commissioned by certified or qualified personnel; any prerequisites for installation to be communicated to the purchaser in advance, in detail.			
<b>12</b>	<b>Documentation</b>			
12.1	The bidder should submit the original brochure or e-copy.			
12.2	User (Operating) Service (Technical / Maintenance) manual in English manual in English			
12.3	Bidders must completely fill the Technical Specification Form (TSF). Only YES/NO/COMPLY should not be written. Page number in the catalogue must be clearly mentioned and highlighted.			
	<b>Technical Status</b>			


*[Signature]*  
Biomedical Engineer



**Technical Specifications of Auxiliary Crutches**

S.N.	Purchaser's Specifications	Bidder's Compliance sheet		
		Compliance Yes/No	Deviation (if any)	Corresponding page no. of data sheet/catalogue in support of specification
	<b>Auxiliary Crutches</b>			
	<b>Manufacturer</b>			
	<b>Brand</b>			
	<b>Type / Model</b>			
	<b>Country of Origin</b>			
<b>1</b>	<b>Description of Function</b>			
1.1	Generally for a long term use, partial weight bearing single lower limb, functional upper limbs			
<b>2</b>	<b>Operational Requirements</b>			
2.1	It shall be used in case of leg injury, fracture, paralysis, muscle/nerve damage, strains/sprains or for post-operative rehabilitation following surgeries of hip, knee or ankle.			
<b>3</b>	<b>System Configuration</b>			
3.1	A pair of auxiliary crutches to assist in mobility with adjustable heights to be used for patients of different height.			
<b>4</b>	<b>Technical Specifications</b>			
4.1	High quality aluminium tube with aluminium alloy treatment on surface.			
4.2	Specially designed expansion tube providing more convenience for adjustment.			
4.3	There's rubber tube inside so as to prevent from friction of metal tube.			
4.4	Anti-skidding rubber feet-pad with metal gasket inside makes it more durable			
4.5	Gears for height adjustment (gear distance: 2.5 cm approx.)			
<b>5</b>	<b>Accessories, spares and consumables</b>			
5.1	All standard accessories, consumables and parts required to operate the equipment, including all standard tools and cleaning and lubrication materials, to be included in the offer. Bidders must specify the quantity of every item included in their offer (including items not specified above).			
<b>6</b>	<b>Operating Environment</b>			
6.1	The system offered shall be designed to be stored and to operate normally under the conditions of the purchaser's country. The conditions include Power Supply, Climate, Temperature, Humidity, etc.			
<b>7</b>	<b>Standards and Safety Requirements</b>			

*Dr. ...*  
*Medical Engineer*



7.1	Must submit ISO 9001 or ISO13485 or CE approved product			
<b>8</b>	<b>User Training</b>			
8.1	Not applicable			
<b>9</b>	<b>Warranty</b>			
9.1	Comprehensive warranty for 1 years after acceptance.			
<b>10</b>	<b>Maintenance Service During Warranty Period</b>			
10.1	During the warranty period supplier must ensure planned preventive maintenance (PPM) along with corrective/breakdown maintenance whenever required.			
<b>11</b>	<b>Installation and Commissioning</b>			
11.1	Not required.			
<b>12</b>	<b>Documentation</b>			
12.1	The bidder should submit the original brochure or e-copy.			
12.2	User (Operating) Service (Technical / Maintenance) manual in English manual in English			
12.3	Bidders must completely fill the Technical Specification Form (TSF). Only YES/NO/COMPLY should not be written. Page number in the catalogue must be clearly mentioned and highlighted. Failure in doing so may lead to the disqualification by the technical team			
	<b>Technical Status</b>			


*[Signature]*  
Biomedical Engineer



**Technical Specification for L stick**

S.N.	Purchaser's Specifications	Bidder's Compliance Sheet		
		Compliance Yes/No	Deviation (if any)	Corresponding page no. of data sheet/ catalogue in support of specification
	<b>L stick</b>			
	<b>Name of bidder</b>			
	<b>Manufacturer</b>			
	<b>Brand</b>			
	<b>Type / Model</b>			
	<b>Country of Origin</b>			
<b>1</b>	<b>Description of Function</b>			
1.1	It is a general-purpose walking aid, which can be used by geriatric, weak patients, or can be as post- operative rehabilitation aid.			
<b>2</b>	<b>Operational Requirements</b>			
2.1	Foldable stick			
<b>3</b>	<b>System Configuration</b>			
3.1	Foldable stick with anti-slip pod.			
<b>4</b>	<b>Technical Specifications</b>			
4.1	Shall be constructed from high strength aluminium alloy tubes.			
4.2	Anti-slip pods ensuring excellent traction, high wear resistance and high resilience.			
4.3	Weight bearing capacity: 120 kgs			
4.4	Height adjustment feature ensures proper load bearing, comfort and correct posture.			
<b>5</b>	<b>Accessories, spares and consumables</b>			
5.2	All standard accessories, consumables and parts required to operate the equipment, including all standard tools and cleaning and lubrication materials, to be included in the offer. Bidders must specify the quantity of every item included in their offer (including items not specified above).			
<b>6</b>	<b>Operating Environment</b>			
6.1	The system offered shall be designed to be stored and to operate normally under the conditions of the purchaser's country. The conditions include Power Supply, Climate, Temperature, Humidity, etc.			
<b>7</b>	<b>Standards and Safety Requirements</b>			
7.1	Must submit ISO 9001 or ISO13485 or CE/ USFDA approved product certificate.			
<b>8</b>	<b>User Training</b>			
8.1	Not required			

*[Signature]*  
Medical Engineer



<b>9</b>	<b>Warranty</b>			
9.1	Comprehensive warranty for 1 year applicable from the date of installation.			
<b>10</b>	<b>Maintenance Service During Warranty Period</b>			
10.1	During the warranty period supplier must ensure corrective/breakdown maintenance whenever required.			
<b>11</b>	<b>Installation and Commissioning</b>			
11.1	Not applicable			
<b>12</b>	<b>Documentation</b>			
12.1	User (Operating) manual in English.			
12.2	Bidder's must submit original catalog			
12.3	Certificate of calibration and inspection from factory.			
12.4	Bidders must completely fill the Technical Specification Form (TSF). Only YES/NO/COMPLY should not be written. Page number in the catalog must be clearly mentioned and highlighted. Failure in doing so may lead to rejection of bid from technical committee.			
	<b>Technical Status</b>			


*[Signature]*  
 Biomedical Engineer



### Technical Specifications of Wheel chair

S.N.	Purchaser's Specifications		Bidder's Compliance sheet		
			Compliance Yes/No	Deviation (if any)	Corresponding page no. of data sheet/ catalogue in support of specification
	Wheel chairs				
	Manufacturer				
	Brand				
	Type / Model				
	Country of Origin				
<b>1</b>	<b>Description of Function</b>				
1.1	Wheel chair is used in hospitals for means of mobility by disabled persons/or persons who have impairments that limit their ability to walk.				
<b>2</b>	<b>Operational Requirements</b>				
2.1	It must be a non-foldable, fixed type adult size wheel chair.				
<b>3</b>	<b>System Configuration</b>				
3.1	Wheel chair fixed type.				
<b>4</b>	<b>Technical Specifications</b>				
4.1	Must be made of the highest quality materials such as Chrome polished finish or stainless steel.				
4.2	Wheels to have braking/locking mechanism and two swivel castors in front.				
4.3	Tire sizes: Rear approx. 600mm (24") solid Mag tyres or Bicycle type spoked wheels, and Front approx. 200mm (8") Mag swivel castors.				
4.4	Armrests: Full, Padded, Fixed height.				
4.5	5cm (approx.) thick , foam cushioned waterproof upholstery and easy to clean.				
4.6	Padded back rest, seat and push handle.				
4.7	Footrests: Fixed height and swing away foot plates made of Aluminium.				
4.8	Maximum Patient weight capacity: approx. 180kg.				
<b>5</b>	<b>Accessories, spares and consumables</b>				
5.1	All standard accessories, consumables and parts required to operate the equipment, including all standard tools and cleaning and lubrication materials, to be included in the offer. Bidders must specify the quantity of every item included in their offer (including items not specified above).				
<b>6</b>	<b>Operating Environment</b>				
6.1	The system offered shall be designed to be stored and to operate normally under the conditions of the purchaser's country. The conditions include Power Supply, Climate, Temperature, Humidity, etc.				
<b>7</b>	<b>Standards and Safety Requirements</b>				
7.1	Must submit ISO 9001 or ISO13485 or CE approved product certificate				
<b>8</b>	<b>User Training</b>				

  
 Medical Engineer



8.1	Not applicable			
<b>9</b>	<b>Warranty</b>			
9.1	Comprehensive warranty for 1 years after acceptance.			
<b>10</b>	<b>Maintenance Service During Warranty Period</b>			
10.1	During the warranty period supplier must ensure planned preventive maintenance (PPM) along with corrective/breakdown maintenance whenever required.			
<b>11</b>	<b>Installation and Commissioning</b>			
11.1	The bidder must arrange for the equipment to be installed and commissioned by certified or qualified personnel; any prerequisites for installation to be communicated to the purchaser in advance, in detail.			
<b>12</b>	<b>Documentation</b>			
12.1	User (Operating) manual in English manual in English			
12.2	The bidder should submit the original brochure or e-copy.			
12.6	Bidders must completely fill the Technical Specification Form (TSF). Only YES/NO/COMPLY should not be written. Page number in the catalogue must be clearly mentioned and highlighted.			
	<b>Technical Status</b>			

*Signature*

Biomedical Engineering